

EXHIBIT

12

Exhibit E

A APPROVED
B APPROVED AS NOTED
C REVISE & RESUBMIT
D REJECTED

[illegible]

RECEIVED

APR 14 2000

~~TDX CONSTRUCTION~~

EXHIBIT

T35

8019215

PENGAD 800-631-6989

ARCHITECT'S REMARKS:

INSTRUCTION MANAGER'S REMARKS:

T E C H N I C A L D A T A

CONTRACT # 16
 TITLE SELF LEVELING UNDERLAYMENT
 SUB. # 03551-0001-01 Self-finishing and Leveling Composition
 4/5/00

RECEIVED
 APR - 7 2000

(FOR FLOOR LEVELING CHANGE ORDER)

Description

Conflow is a self-leveling and self-finishing polymer modified Portland Cement based material. Use Conflow as an underlayment for interior applications.

2. Areas with heavy or loose cutback must be removed.
3. Shot blasting is recommended.
4. Use Conspec Orange Peel to remove any residual cutback.

File and Taping Instructions

BARUCH ACADEMIC COMPLEX 66 LEXINGTON AVENUE NEW YORK, N.Y.		
<input checked="" type="checkbox"/>	A ACTION	APPROVED
<input type="checkbox"/>	B ACTION	APPROVED AS NOTED Resubmit for Record Purposes Only
<input type="checkbox"/>	C ACTION	REVISE AND RESUBMIT
<input type="checkbox"/>	D ACTION	REJECTED
<p>Reviewing is only for conformance with the design concept of the project and compliance with the information given in the contract documents. The contractor is responsible for dimensions to be confirmed and correlated at the site, for information that pertains solely to the fabrication processes or to the means, methods, techniques, experiences and procedures of construction, and for coordination of the work of all trades.</p> <p>KOHN PEDERSEN FOX ASSOCIATES P.C. Date <u>4-13-00</u> By <u>ML</u></p>		
<u>03551</u> SECTION	<u>01</u> FILE NO.	<u>01</u> SUBMISSION

RECEIVED

APR 14 2000

TDX CONSTRUCTION

EXHIBIT 'E'

the
 good
 in force
 ANG
 LIEU OF ANY
 WARRANTIES
 OR A
 WARRANTIES
 ON OF LAW, COURSE
 OR OTHERWISE. As the
 Warranty, we will replace
 however, that the buyer examines the
 promptly notify us in writing of any
 are used or incorporated into a
 months after Conspec Marketing &
 inc. has shipped the materials, all our
 or duties with respect to the quality of the
 and shall conclusively be presumed to have been
 liability therefore terminates, and no action for breach
 may thereafter commence. Conspec Marketing &
 acuring Co., Inc. shall in no event be liable for
 sequential damages. Unless otherwise agreed to in writing, no
 warranty is made with respect to materials not manufactured by
 Conspec Marketing & Manufacturing Co., Inc. We cannot
 warrant or in any way guarantee any particular method of use of
 application or the performance of materials under any particular
 condition. Neither this Warranty nor our liability may be extended
 or amended by our salespeople, distributors or representatives or
 by any sales information or drawings.

Receiving

All bagged products should be checked for dryness prior to signing shipping papers.

Storage

Conflow should be stored in a cool, dry interior area. At no time should material be exposed to high moisture, rain or snow conditions.

Fax-On-Demand

Request Document 1000 for a complete Index of Conspec Product Information. For Conflow documents request 1525 for Literature and 1526 for the MSDS.



Fax-On-Demand

0608098

Packaging

45 lb. triple lined bag (20.4 kg)

Limitations/Precautions

DO NOT place at temperatures below 50°F(10°C) or if the temperature is expected to fall below 50°F(10°C) in the next twenty-four hour period. Severe variation of 1" (2.54 cm) or more over 1" (.30 m) or less should be referred to manufacturer for proper procedure. Wind over 5 m.p.h. can dehydrate Conflow and cause cracking. Unless area of application can be

ans
 drying
 eas should be
 24 hours
 to traffic. If the
 eeds 48 hours or there

various types of pumps
 available for the application of
 with your local representative
 as, availability and recommenda-

It
 us
 the
 tes in
 pment and
 ce to continuously



CONSPEC®

NSPEC Marketing & Manufacturing Co., Inc. • 636 S. 66th Terrace • Kansas City, KS 66111 • 913-287-1700 • 800-348-7351

DASNY_TRAVELERS2 228521
 DASNY_TRAVELERS2 228521